

King TAPE

- Aftermarket Auto Refinishing
- Ship Grade High Tack
- Solvent Resistant



Applications

- Designed for use in automobile refinish industry

Features

- Easy to apply and unwind
- Superior Adhesive strength offers quick stick on applications
- Highly flexible, great conformability on concern or uneven surface
- Maximum temperature resistance can be up to 100° C/ 1 hrs.

Physical Properties

Backing:	Crepe Peper
Adhesive System:	Rubber Solvent
Total Thickness (mm):	0.15 ± 0.01
Tensile Strength (kg/25mm):	8 ± 0.2
Elongation	12 ± 2%
Adhesion to Stainless Steel (g/25mm)	700 (above)
Initial Tack	18 (above)
Temperature Resistance:	100°C x 1 hr

Queen TAPE

made in USA

- Economy Grade
- General Purpose
- Pressure Sensitive
- Rubber Solvent Based



Applications

- Bonding, sealing, joining and light duty masking tape
- Widely apply in stationery, packaging and industrial areas

Features

- Easy to apply and unwind
- Superior Adhesive strength offers quick stick on applications
- Highly flexible, great conformability on concern or uneven surface
- Maximum temperature resistance can be up to 100° C/ 1 hrs.

Physical Properties

Backing:	Crepe Peper
Adhesive System:	Rubber Solvent
Total Thickness (mm):	0.14 ± 0.01
Tensile Strength (kg/25mm):	8 ± 0.2
Elongation	12 ± 2%
Adhesion to Stainless Steel (g/25mm)	700 ± 100
Initial Tack	18 (above)
Temperature Resistance:	80°C x 30 min.